



Main Specifications

- 材质硬度 (material hardness) : C1100-HBS120
- 缝隙 (CREVICE): 焊接 (WELDING)
- 镀层厚度 (PLATING THICKNESS): 2.5um-5um
- 镀层耐温 (COATING TEMPERATURE): 120° /2Hour
- 接线类型 (Wiring type): 多股线 (Stranded)
- 最大电流 (MAX CURRENT): 62A (6.0m-10m²)

Part No	Wire Range	STUD SIZE		ITEM NO.	DIMENSION mm (mm/25.4=inch)								Material	Finish	Qty/bag	Remark
	A. W. G (mm ²)	METRIC	AMERICAN		D	L	W	F	H	B	E	T				
S0101TB-RTF	8 (8)	4	#8	RBN 8-4L	4.3	23.5	12.0	9.0	7.2	4.5	8.5	1.2	T2 (Red Copper)	Mist tin plating	500	
S0102TB-RTF	8 (8)	5	#10	RBN 8-5M	5.3										500	
S0103TB-RTF	8 (8)	6	1/4"	RBN 8-6S	6.4										500	
S0104TB-RTF	8 (8)	4	#8	RBN 8-4S	4.3	21.5	8.0	500								
S0105TC-RTF	8 (8)	3.5	#6	RBN 8-3.7	3.7			500								

GTER ® 东莞市高嘉精密电子有限公司 DONGGUAN GJ PRECISION ELECTRONICS Co.,Ltd.	APPROVED BY: APPROVED	PROJ:	TOLERANCE	LTR	REVISION RECORD		NAME	DATE
	CHECKED BY: CHECKED	UNIT: mm	-1 ±0.10	标记1	修改内容1	姓名1	日期1	
	DRAWN BY: yiliangdong	SCALE: --	1-5 ±0.15	标记2	修改内容2	姓名2	日期2	
	DATE: 2024-12-18	SHEET: 1/1 A4	5-15 ±0.20	标记3	修改内容3	姓名3	日期3	
	PART NO: GJ-S01*TC-RTF	非绝缘端子 产品图	SHEET: 1/1 A4	15-30 ±0.25	标记4	修改内容4	姓名4	日期4
non-insulated ring terminal	S000*TC-RTF端子 产品图	VER NO: A0	30- ±0.30	CUSTOMER: ---		Conforms to The RoHS&REACH Instruction		
			(ANGLE) X ±10°					

规格表