

产品规格书

PRODUCT SPECIFICATION

产品规格： GJ-C4201 DIP 單雙排空接系列	No.: EN-003(2017-08)	Date Issued: 2017/08/01
Specification: GJ-A4201 DIP Series	Rev. : A.0	Date Revised:
4.20mm series wire to wire connector		Issued by: Engineering Dept.

Prepared by: <i>James.Kang</i>	Checked by: <i>James.Kang</i>	Reviewed by:	Approved by: <i>Liangdong.Yi</i>
-----------------------------------	----------------------------------	--------------	-------------------------------------

This document contains information that is proprietary to Gaojia Precision Electronics Not should not be used without written permission.

地址：广东省东莞市沙田镇沙田大道263号3单元101室

Add: Room 101, Unit 3, No.263, Sha Tin Avenue, Sha Tin Town, Dongguan City, Guangdong Province

电话：0769-81669553 传真：0769-81669553



Type Document	Product Specification	Revised /Edition	M
Date Issued	2004/01/20	Data Revised	2017/06/13
Subject :GJ-A4201TF-BTS GJ-A4201HF-XX GJ-A4201HF-2*XX GJ-C4201TM-BTS GJ-C4201HM-XX GJ-C4201HM-2*XX Pitch : 4.20mm (Dual-Row & Single-Row) Wire to Wire Power Connector Series.			Issued By: Engineering Dept.

This specification is referred to 4.20mm (Dual-Row & Single-Row) series wire to wire Power connector.

本規格書內容係提供 4.20 mm (迷你型插座組合 ; 雙排與單排)系列產品相關參考 , 其用途為電線端相接於電線端之動力電源連接器

-INDEX-

- 1.0 Product Name/Part Number & Drawing Number. (產品名稱 / 產品型號及圖面型號)
- 2.0 Construction/Dimensions/Material & Surface Finish.(材質以及表面鍍層)
- 3.0 Characteristic.(產品特性)
- 4.0 Specimen.(樣本圖示)
- 5.0 Applicable Standards.(適用規範)
- 6.0 Mechanical Performance.(機械性能)
- 7.0 Electrical Performance.(電氣性能)
- 8.0 Environmental Performance.(環境性能)
- 9.0 Insertion Force (I.F.) & Withdrawal Force (W.F.) for user reference(插入力與拔出力參考規格)
- 10.0 Remark (備註)

REV. (版次)	Revision Record (改版變更原因)	Date(日期)	ECN No.
C	增加中文敘述 以及增加版次變更註記欄	2010/01/27	EC2010-01-037
D	增加JS-1149-TP/TP1 ; JS-1148-TP/TPL	2010/12/23	EC2010-12-010
E	鹽水噴霧週期以電鍍方式區隔為 8 小時與24 小時	2011/05/19	EC2011-05-032
F	增加 Thumb Latch Operation Force ; Thumb Latch Yield Force 兩項規格	2011/08/26	EC2011-08-004
G	增加 Polyamide 6 UL 94 V2 ; 增列 AWG 與電流對照 及額定電壓	2012/01/13	EC2012-01-010
H	新增 Female Crimp Terminal (With AWG #20~24 is applied) JS-1149-TPL	2012/04/11	EC2012-04-014
I	P/N 增加(V0)選項	2013/11/01	EC2013-11-001
J	1 增訂 3.5 項 Storage of Package 以及 3.6 項 Floor Life 2. 6.1 項 Insertion & Withdrawal Force Table1. 增訂 3 & 5 Poles	2014/04/17	EC2014-04-017
K	增訂 8.7 項 Cold 耐寒試驗	2014/12/31	EC2014-12-031
L	依 ECR-00000160 修改產品敘述	2016/10/21	EC2016-10-021
M	1增訂8.8項Salt Spray鹽水噴霧 2刪除BSI標示	2017/06/13	EC2017-06-013



Type Document	Product Specification	Revised /Edition	M
Date Issued	2004/01/20	Data Revised	2017/06/13
Subject :GJ-A4201TF-BTS GJ-A4201HF-XX GJ-A4201HF-2*XX GJ-C4201TM-BTS GJ-C4201HM-XX GJ-C4201HM-2*XX Pitch : 4.20mm (Dual -Row & Single-Row) Wire to Wire Power Connector Series.			Issued By: Engineering Dept.

1.0 Product Name/Part Number & Drawing Number(產品名稱 / 產品型號及圖面型號): Note: (xx) The number of the circuits

Product Name(產品名稱)	Part Number(產品型號)	Drawing Number(圖面型號)
Female Crimp Terminal (With AWG #16~24 is applied)	GJ-A4201TF-BTS	
Male Crimp Terminal (With AWG #16~24 is applied)	GJ-C4201TM-BTS	
Receptacle (Double Row) 雙排插座	GJ-A4201HF-2*XX	
Receptacle (Single Row) 單排插座	GJ-A4201HF-XX	
Plug (Double Row) 雙排插頭	GJ-C4201HM-2*XX-WD	
Plug (Single Row) 單排插頭	GJ-C4201HM-XX-WD	
Plug (Without Ear ; Double Row) 雙排插頭 ; 無耳	GJ-C4201HM-2*XX-A&B	
Plug (Without Ear ; Single Row) 單排插頭 ; 無耳	GJ-C4201HM-XX-A&B	

2.0 Construction/Dimensions/Material & Surface Finish(材質以及表面鍍層):

Part Name(零件名稱)	Material(材質)	Surface Finish(表面鍍層)
Crimp Terminal (柳壓端子)	GJ-A4201TF-BTS	Brass
		Phosphor Bronze
	GJ-C4201TM-BTS	Brass
		Phosphor Bronze
Plug (插頭) ; Receptacle (插座)	Polyamide 66	UL 94V-2 or 94V-0

3.0 Characteristic(產品特性):



Item(項目)	Standard(標準規範)							
3.1 額定電流 Rated Current	Conductor Size	AWG	16#	18#	20#	22#	24#	
		Area(mm ²)	1.31 mm ²	0.865 mm ²	0.534 mm ²	0.342 mm ²	0.220 mm ²	
	Amp AC/DC	7 A		5 A	3 A	2 A		
3.2 額定電壓 Rated	250 V AC/DC							
3.3 Ambient Temperature Range 環境與操作溫度範圍	(操作使用溫度與濕度範圍) Operating Temp. : -40°C~+105°C; 85% R.H. Max Including 30°C Terminal Temperature Rise at rated Current , (包括定額電流內 , 端子所產生 30°C 以下溫昇)							
3.4 Applicable Wire 適用電線	3.4.1	(金屬導體型號) Conductor Construction Size: AWG #16~#24						
	3.4.2	(電線絕緣材質外徑) Wire Insulation O.D.: 1.45mm~2.10mm						

Type Document	Product Specification	Revised /Edition	M
Date Issued	2004/01/20	Data Revised	2017/06/13
Subject :GJ-A4201TF-BTS GJ-A4201HF-XX GJ-A4201HF-2*XX GJ-C4201TM-BTS GJ-C4201HM-XX GJ-C4201HM-2*XX Pitch : 4.20mm (Dual -Row & Single-Row) Wire to Wire Power Connector Series.			Issued By: Engineering Dept.

3.5	Storage of Package 包裝未拆封之保存	Temperature and Humidity Condition 溫濕度條件		Temperature 溫度 : -10℃~+40℃ Percentage Humidity 相對濕度 : 70 % Max
		Term 保存期限	Housing	2 Years
			Crimp Terminal	1 Year
3.6	Floor Life 拆封後使用期限	Crimp Terminal		3 Months

Note: 嵌合面板適用厚度 Applicable Panel Thickness: 2.0 mm Max.

4.0 Specimen(樣本圖示) :

Part Name / Part Number / Picture or Photograph 零件名稱 / 零件型號 / 樣本圖示			
Female Crimp Terminal GJ-A4201TF-BTS		Male Crimp Terminal GJ-C4201TM-BTS	
Receptacle Single-Row GJ-A4201HF-XX		Receptacle Dual-Row GJ-A4201HF-2*XX	
Plug Single-Row with Ear GJ-C4201HM-XX-WD		Plug Dual-Row with Ear GJ-C4201HM-2*XX-WD	
Plug Single-Row without Ear GJ-C4201HM-XX-B		Plug Dual-Row without Ear GJ-C4201HM-2*XX-B	

Type Document	Product Specification	Revised /Edition	M
Date Issued	2004/01/20	Data Revised	2017/06/13
Subject :GJ-A4201TF-BTS GJ-A4201HF-XX GJ-A4201HF-2*XX GJ-C4201TM-BTS GJ-C4201HM-XX GJ-C4201HM-2*XX Pitch : 4.20mm (Dual -Row & Single-Row) Wire to Wire Power Connector Series.			Issued By: Engineering Dept.

5.0 Applicable Standards(適用規範):

ANSI/EIA 364 ; ANSI/EIA/ECA 364 Testing method for electrical connectors.

電子連接器，所適用之 ANSI/EIA 364 ; ANSI/EIA/ECA364 測試規範

6.0 Mechanical Performance(機械性能):

Item(項目)		Test Condition(測試條件)	Requirement(規格)
6.1	Insertion & Withdrawal Force 插座與插頭 嵌入與拔出力	Insert and withdrawal with connectors at the speed rate of 25.4 ± 3mm/minute. 插頭與插座兩端勘合，以每一分鐘 25.4 ± 3 mm 的速率，作嵌入與拔出往返測試 (EIA/ECA 364-13D) (Excluding Thumb Latch 不包含指壓活動卡榫結合力)	Refer to 9.0 Table1. 參照第 9 項 表格 9.1
6.2	Wire Pullout Force(Axial) 電線脫離端子包覆之 拔出力(軸向)	Pull out the cable from contact terminal at the speed rate of 25.4± 3 mm/minute. 對端子所包覆電線，施以每一分鐘 25.4 ± 3 mm 速率之軸向拔出力 (EIA 364-08B)	AWG#16 size wire 9.0kgf/Min.(88.0N 牛頓)
			AWG#18 size wire 8.0kgf/Min.(78.4N 牛頓)
			AWG#20 size wire 6.0kgf/Min.(59.0N 牛頓)
			AWG#22 size wire 4.0kgf/Min.(39.0N 牛頓)
			AWG#24 size wire 3.0kgf/Min.(29.0N 牛頓)
6.3	Crimp Terminal Retention Force (in Receptacle or Plug) 插座或插頭與 錫線端子間拔出力	Axial pullout force on the terminal in the Receptacle or Plug at the speed rate of 25.4 ± 3 mm per minute. 對於已經存在於插座或是插頭當中錫線端子，施以每一分鐘 25.4 ± 3 mm 速率之軸向拔出力 (EIA/ 364-05)	單一導體 Per Contact 最小容許值 3.0kgf/Min.
6.4	Panel Mount Retention 有耳插座與嵌合面板間 拔出力	Full mate and then unmate the Connectors at a rate of 25 .4± 3 mm per minute. 將插座緊密地嵌入面板當中，然後再以每一分鐘 25.4 ± 3 mm 速率將插座與面板脫離，並量測最終拔出力	最小容許值 16.0kgf/Min.
6.5	Thumb Latch Operation Force 指壓活動卡榫推進力	Depress Latch at a Speed rate of 25.4 ± 3 mm per minute. 以每一分鐘 25.4 ± 3 mm 的速率，將活動卡榫推達定位	最大容許值 1.7kgf/Max
6.6	Thumb Latch Yield Force 指壓活動卡榫降伏力	Mate loaded connectors fully. Pull connectors apart at the speed rate of 25 .4± 3mm per minute. 將連接器兩端緊密互配，而後以每一分鐘 25.4 ± 3 mm 的速率，將活動卡榫拔出測試	最小容許值 6.9kgf/Min.

Type Document	Product Specification	Revised /Edition	M
Date Issued	2004/01/20	Data Revised	2017/06/13
Subject :GJ-A4201TF-BTS GJ-A4201HF-XX GJ-A4201HF-2*XX GJ-C4201TM-BTS GJ-C4201HM-XX GJ-C4201HM-2*XX Pitch : 4.20mm (Dual -Row & Single-Row) Wire to Wire Power Connector Series.			Issued By: Engineering Dept.

7.0 Electrical Performance(電氣性能) :

Item(項目)	Test Condition(測試條件)	Requirement(規格)
7.1 Contact Resistance (低階信號) 接觸阻抗	A maximum voltage of 20mV and a maximum current of 100mA are applied to the mate connector. 對組合狀態下連接器，於其兩端施以最大測試電壓 20mV 以及最大測試電流 100mA (EIA/ECA 364-23C) (Does not include wire resistance 不包含電線阻抗)	Contact Resistance: 20 milliohms Max. 最大容許值. 20 毫歐姆
7.2 Insulation Resistance 絕緣阻抗	Apply 500V D/C for 1 minute between adjacent contacts to measure the insulation resistance. 對相鄰兩接觸導體，於一分鐘時間內施予 500V D/C 電壓，並量測其間絕緣阻抗值 (EIA 364-21C)	Insulation Resistance: Initial 1000megohms Min 最初容許值. 1000 兆歐姆
7.3 Withstanding Voltage 耐電壓	Apply 1500V A/C (rms) for 1 minute and the leakage current shall not exceed 0.5mA to the adjacent terminal and ground of the mate connectors. 對組合狀態下連接器，於其相鄰兩導體末端各施以電壓 1500V A/C(實效值) 時間 1 分鐘，且漏電流必須小於 0.5mA(毫安培) (EIA 364-20C)	No breakdown or flashover. 無損毀或者產生火花

8.0 Environmental Performance(環境性能) :

Item(項目)	Test Condition(測試條件)	Requirement(規格)
8.1 Durability 耐久性	Mate Connectors up 50 Cycles at a Maximun rate of 10 cycles Per minute prior to environmental test (EIA/ECA 364-09C) 以組合狀態下連接器且未經環境測試，依每分鐘內進行 10 次嵌入與拔出之最大速率，連續 50 次嵌入與拔出往返測試	(After the test) Contact resistance : 40 mΩ Max 經耐久性試驗後接觸阻抗 最大容許值 40 毫歐姆
8.2 Temperature Rise (Via Current Cycling) 溫度上昇 (經由電流循環操作)	Mate connector . measure the temperature rise of contact when the maximum rated current is passed 以組合狀態下連接器，通過最大容許電流 量測其導體溫度上昇值 (EIA 364-70B Conditions 1 . Method 1)	Mate connectors Temperature Rise: +30°C/Max. 組合狀態下之連接器溫度上昇 最大容許值 +30°C



Type Document	Product Specification	Revised /Edition	M
Date Issued	2004/01/20	Data Revised	2017/06/13
Subject :GJ-A4201TF-BTS GJ-A4201HF-XX GJ-A4201HF-2*XX GJ-C4201TM-BTS GJ-C4201HM-XX GJ-C4201HM-2*XX Pitch : 4.20mm (Dual -Row & Single-Row) Wire to Wire Power Connector Series.			Issued By: Engineering Dept.

Item(項目)	Test Condition(測試條件)	Requirement(規格)
8.3 Vibration 耐振動	<p>A mated connector shall be mounted on a printed Circuit board and subjected to a vibration test of the following conditions.</p> <p>During the test, test current continuity shall be checked. After the test, contact resistance shall be measured.</p> <p>(EIA/ECA 364-28E-Condition I)</p> <p>以組合狀態下連接器焊接於電路板作為試驗樣品,依照隨附如下規格要求,進行耐振動試驗,試驗過程中確認是否產生不連續電流(斷電)現象,並於試驗過後量測其接觸阻抗。</p> <p>Frequency(頻率): 10~55~10 Hz/minute.</p> <p>Amplitude (振幅): 1.5 mm P-P</p> <p>Direction (方向): 1. Axis of up and down.上下軸向(Y 軸) 2. Axis of right the left. 左右軸向(X 軸) 3. Axis of front and back.前後軸向(Z 軸)</p> <p>Period(週期): 2 hours for each direction. (每一個軸向持續 2 小時)</p>	<p>Initial Contact Resistance :</p> <p>20 milliohms Max.</p> <p>接觸阻抗最初容許值 20 毫歐姆</p> <p>(After the test)</p> <p>Contact Resistance:</p> <p>40 milliohms Max.</p> <p>經耐振動試驗後接觸阻抗 最大容許值 40 毫歐姆</p>
8.4 Humidity 恆溫恆濕	<p>A mated connector shall be placed in a humidity chamber of the following conditions. After the test, leave the specimen at room temperature for 1~2 hours before the contact resistance, the insulation resistance and the dielectric withstanding voltage shall be measured.</p> <p>(EIA 364-31B Conditions III . Method A)</p> <p>以組合狀態下連接器放置於恆定溫度與濕度的空間,依照隨附如下規格要求,進行恆溫恆濕試驗,經試驗過後將樣品置於室溫 1~2 小時,再量測其接觸阻抗、絕緣阻抗、以及耐電壓測試。</p> <p>Temperature(溫度): 40±2°C.</p> <p>Relative Humidity(相對濕度): 90%~95% (RH).</p> <p>Period(週期): 96 hours continuously. (持續 96 小時)</p>	<p>(After the test)</p> <p>Contact Resistance:</p> <p>40milliohms Max.</p> <p>經恆溫恆濕試驗後接觸阻抗 最大容許值 40 毫歐姆</p> <p>(After the test)</p> <p>Insulation Resistance :</p> <p>100Megohms Min.</p> <p>經恆溫恆濕試驗後絕緣阻抗 最小容許值. 100 兆歐姆</p> <p>經恆溫恆濕試驗後測耐電壓</p> <p>(After the test)</p> <p>Withstanding Voltage:</p> <p>1500V A/C for 1 minute</p>



Type Document		Product Specification	Revised /Edition	M
Date Issued		2004/01/20	Data Revised	2017/06/13
Subject :GJ-A4201TF-BTS GJ-A4201HF-XX GJ-A4201HF-2*XX GJ-C4201TM-BTS GJ-C4201HM-XX GJ-C4201HM-2*XX Pitch : 4.20mm (Dual -Row & Single-Row) Wire to Wire Power Connector Series.				Issued By: Engineering Dept.
Item(項目)	Test Condition(測試條件)		Requirement(規格)	
8.5	Thermal Shock 冷熱衝擊	<p>A mated connector shall be subjected to a thermal shock test of the following conditions. After the test, leave the specimen at room temperature for 1~2 hours before the contact resistance, the insulation resistance and the dielectric withstanding voltage shall be measured.</p> <p>以組合狀態下連接器作為試驗樣品, 依照隨附如下規格要求, 進行冷熱衝擊試驗, 經試驗過後將樣品置於室溫 1~2 小時, 再量測其接觸阻抗、絕緣阻抗、以及耐電壓測試。</p> <p>One Cycle Consists Of: (EIA/ECA 364-32D)</p> <p>-55°C+0/-3°C for 30 minutes. → Room Temp. 5 minutes 85°C+3/-0°C for 30 minutes. → Room Temp. 5 minutes</p> <p>Total Cycles: 5 Cycles. 以-55°C+0/-3°C溫度持續 30 分鐘, 經室溫 5 分鐘, 而後再以 85°C+3/-0°C溫度持續 30 分鐘, 再經室溫 5 分鐘, 構成一次冷熱循環, 總計循環次數 5 次。</p>	Same as paragraph 8.4 同 8.4 章節	
8.6	Thermal Aging 高溫老化試驗	<p>A mated connector shall be placed in a heat oven of the following conditions. After the test, leave the specimen at room temperature for 1~2 hours before the contact resistance shall be measured. 以組合狀態下連接器放置於加熱烤箱當中, 依照隨附如下規格要求, 進行高溫老化試驗, 經試驗過後將樣品置於室溫 1~2 小時,再量測其接觸阻抗。</p> <p>Temperature(溫度): 105±2°C. (EIA 364-17B)</p> <p>Period(週期): 96 hours continuously . (持續 96 小時)</p>	Initial Contact Resistance : 20 milliohms Max. 接觸阻抗最初容許值 20 毫歐姆 (After the test) Contact Resistance : 40milliohms Max. 經高溫老化試驗後接觸阻抗 最大容許值 40 毫歐姆	
8.7	Cold 耐寒試驗 (Low Temperature)	<p>A mated connector shall be placed in a cold chamber of the following conditions. After the test, leave the specimen at room temperature for 1~2 hours before the contact resistance shall be measured. 以組合狀態下連接器放置於低溫空間內, 依照隨附如下規格要求, 進行耐寒試驗, 經試驗過後將樣品置於室溫 1~2 小時,再量測其接觸阻抗。(EIA 364-59A Condition D ; Condition 3)</p> <p>Temperature(溫度): -40±3°C.</p> <p>Period(週期): 96 hours continuously . (持續 96 小時)</p>	Initial Contact Resistance : 20 milliohms Max. 接觸阻抗最初容許值 20 毫歐姆 (After the test) Contact Resistance : 40 milliohms Max. . 經耐寒試驗後接觸阻抗 : 最大容許值. 40 毫歐姆	



Type Document	Product Specification	Revised /Edition	M
Date Issued	2004/01/20	Data Revised	2017/06/13
Subject : GJ-A4201TF-BTS GJ-A4201HF-XX GJ-A4201HF-2*XX GJ-C4201TM-BTS GJ-C4201HM-XX GJ-C4201HM-2*XX Pitch : 4.20mm (Dual -Row & Single-Row) Wire to Wire Power Connector Series.			Issued By: Engineering Dept.

Item(項目)	Test Condition(測試條件)	Requirement(規格)
8.8 Salt Spray 鹽水噴霧	<p>A mated connector shall be subjected to a Salt Spray test of the following conditions. After the test , the specimen shall be washed with running water and dried naturally before the measurement of contact resistance. 以組合狀態下連接器作為試驗樣品, 依照隨附如下規格要求, 進行鹽水噴霧試驗 , 試驗過後將樣品用清水沖洗並經過自然風乾 , 而後量測其接觸阻抗。(EIA 364-26B Conditions B)</p> <p>Density(鹽水密度) : 5 % in weight. Temperature(溫度) : 35±2°C.</p> <p>Period(週期): Terminal or contact (Stamping after tin plated for 8 hours) ; Terminal or contact (Stamping before tin plated for 24 hours) 端子或導體 (先電鍍後沖壓 8 小時) ; 端子或導體 (先沖壓後電鍍 24 小時)</p> <p>Salt spray test only define the plating area,without plating area (as copper cross section) will not be defined. 鹽水噴霧測試只判定電鍍區域,無電鍍區域(如折斷面裸銅)則不做判定</p>	<p>Initial Contact Resistance : 20 milliohms Max. 接觸阻抗最初容許值 20 毫歐姆</p> <p>(After the test) Contact Resistance: 40 milliohms Max. 經鹽水噴霧試驗後接觸阻抗最大容許值 40 毫歐姆</p>

Notes : Flowing Mixed Gas (EIA 364-65A) shall be conduct by Customer request 混合流動氣體測試遵照客戶需求

9.0 Tables & Attachments

9.1 Table 1. Insertion Force (I.F.) & Withdrawal Force (W.F.) for user reference:

No. of Circuits 極數	AT INITIAL 首次嵌入與拔出(初始值)		AT 50 TH 50 次嵌入與拔出之後	No. of Circuits 極數	AT INITIAL 首次嵌入與拔出(初始值)		AT 50 TH 50 次嵌入與拔出之後
	I.F. (MAX) 嵌入力	W.F. (MIN) 拔出力	W.F. (MIN) 拔出力		I.F. (MAX) 嵌入力	W.F. (MIN) 拔出力	W.F. (MIN) 拔出力
	02	3.00	0.20		0.15	12	18.00
03	4.50	0.30	0.23	14	21.00	1.40	1.05
04	6.00	0.40	0.30	16	24.00	1.60	1.20
05	7.50	0.50	0.38	18	27.00	1.80	1.35
06	9.00	0.60	0.45	20	30.00	2.00	1.50
08	12.00	0.80	0.60	22	33.00	2.20	1.65
10	15.00	1.00	0.75	24	36.00	2.40	1.80

Unit : kg/f

10.0Remark(備註) : Any change or revision for the product specification will not be announced in advance.

Please contact our sales representative for the latest information.

有關規格書內容經變更或改版, 如未能夠及時發佈與通知, 煩請連絡我司業務人員以提供產品最新資訊

Reviewed: James.Hang Approved: James.Hang Verified: Liangdong.Yi